

<b>PRODUCT:</b>	<b><u>METRO MOVES</u></b>
<b>DESCRIPTION:</b>	Level Loop Graphics
<b>PILE CONTENT:</b>	100% Wool
<b>FIBRE QUALITY:</b>	Averaging not finer than 33 microns
<b>YARN CONSTRUCTION:</b>	2 Ply
<b>TOTAL PILE WEIGHT:</b>	1360 gms/m <sup>2</sup> - 40oz/ yd <sup>2</sup> (Tolerance + 5%)
<b>PILE HEIGHT:</b>	5.5mm
<b>MACHINE GAUGE:</b>	1/10
<b>PRIMARY BACKING:</b>	Woven Polypropylene
<b>SECONDARY BACKING:</b>	7oz Jute
<b>PATTERN REPEAT:</b>	5mm
<b>CARPET WIDTH:</b>	366cm/ 12 foot Untrimmed
<b>RATING:</b>	Commercial Heavy Duty & Stairs
<b>EARLY FIRE HAZARD: AS 1530 PART III</b>	Ignitability 14 Spread of Flames 0 Heat Evolved 0 Smoke Developed 5
<b>EXTRACTABLE MATTER: DICHLOROMETHANE EXTRACT IWS TM 136</b>	1.5 Maximum
<b>TUFT WITHDRAWAL FORCE: IWS TM202</b>	30 Newtons (Minimum)
<b>SECONDARY BACKING ADHESION: IWS TM264</b>	40 Newtons (Minimum)
<b>COLOUR FASTNESS TO LIGHT: IWS TM 133</b>	4-5 (Subject to Colour Selection)
<b>COLOUR FASTNESS TO SHAMPOO: IWS TM233</b>	3-4 (Minimum)
<b>COLOUR FASTNESS TO RUBBING: IWS TM232</b>	3-4 Minimum (Subject to colour Selection)

**Contact Details**

Godfrey Hirst NZ Limited, 142 Kerrs Road, Wiri, Manukau City, 2104  
Freephone: 0800 500 210  
Freefax 0800 500 310  
Website: [www.godfreyhirst.co.nz](http://www.godfreyhirst.co.nz)